



110 cbm/h
Einspülung regelbar

170 cbm/h
50 cbm/h
120 cbm/h
130 cbm/h
80 cbm/h

550 cbm/h
4.1

2.18 U/K
2.17 0/1
2.16 0/2
2.15 0/2

Haldenentwässerung 30 cbm/h

zur Kläranlage
4.2

3.8 40 l/h
3.9 15 l/h
3.10 15 l/h

Haldenentwässerung 10 cbm/h

510 cbm/h

Holz

32/120

110 cbm/h
anteilig 0/2

20 cbm/h

210 cbm/h

80 cbm/h

120 cbm/h

130 cbm/h

200 l/h 0/2
50 cbm/h

40 l/h 0/2
40 cbm/h

240 l/h 0/2
270 cbm/h

130 cbm/h

100 cbm/h

250-300 l/h 0/120

1 l/h
20-80 l/h

2/32
3.1
3.2

3.3

16
8
2

20-80 l/h 2/32

16
8
2

3.7

3.4

3.5

3.6

1.1

1.2

1.4

1.3

2.1

2.2

2.3

2.4

2.7

2.8

2.5

2.6

2.11

2.12

2.14

2.13

2.15

2.16

2.17

2.18

2.10

3.8

3.9

3.10

4.2